

### KEY FEATURES

Familiar, easy-to-use, smartphone form factor

Works with professional software for GIS workflows

Big, sunlight-readable screen

Stay in touch with the office—integrated communications available

Rugged for work in all conditions

1D/2D barcode scanner version available



### WORK SMART WITH SMARTPHONE-INSPIRED MOBILE GIS

Your team will perform better when they've got the tools they need to get the job done. Trimble® Juno® 5 series handhelds combine must have functionality with the familiarity of a smartphone form-factor.

Compatible with GIS-oriented Trimble workflows, the Juno 5 is the smart solution your team can trust for standardizing inspections and asset management.

#### Bringing GIS out to the field

Perfect for asset management and data maintenance projects, everything is integrated into a convenient, rugged package: high-sensitivity GNSS, Windows® Embedded Handheld operating system, Office applications, camera, and cellular connectivity.



Stay flexible and connected with the optional built-in communications to send and receive calls and data on the job, keeping your team productive, informed, and in touch.

Using the professional workflows of Trimble field and office software, you can work with confidence in the data you are capturing.

#### A smarter approach to field productivity

It may look like a smartphone, but the Juno 5 series is all business. Rugged enough to meet military specs, with an IP65 rating. It has a large screen so you can easily view data or photos even in direct sunlight.

You can be confident that your teams have a real, professional tool—built to work in even the toughest conditions.



#### Barcode Option

If your workflow includes 1D or 2D barcodes, choose the Juno 5 Barcode handheld. Trimble's Scan Agent software lets you customize the scanner features to fit your needs.

The Trimble Juno 5 combines the convenience of a smartphone with professional rugged design, for true confidence in the field. This makes the Trimble Juno 5 series the tool of choice for flexible, real world asset management and GIS data updates.

# TRIMBLE JUNO 5 SERIES

## PRODUCT MODELS

	Juno 5B / Juno 5B barcode	Juno 5D / Juno 5D barcode
Cellular voice & data	No	Yes

## STANDARD FEATURES

### System

- Integrated 3.75G cellular data, text, and voice capability (Juno 5D only)
- 8 megapixel camera with geotagging and dual LED flash
- Bluetooth® v2.1 with enhanced data rate
- Wi-Fi (802.11b/g/n)
- Multi-touch 4.3 inch WVGA sunlight-readable Gorilla® glass display
- Long-life, rechargeable Li-Ion battery
- 800 MHz (Juno 5B) or 1 GHz (Juno 5D), Texas Instruments DM3730 processor
- 256 MB (Juno 5B) or 512 MB (Juno 5D) RAM
- 8 GB (Juno 5B) or 16 GB (Juno 5D) Flash storage
- MicroSD memory card slot (supports SDHC up to 32 GB)
- Integrated speaker and microphone
- Windows Embedded Handheld 6.5 in Chinese (Simplified), English, French, German, Italian, Japanese, Korean, Portuguese (Brazilian), Russian, or Spanish

### GPS

- High-sensitivity GPS/SBAS<sup>1</sup> receiver and antenna

### Standard Software

- Microsoft® Office Mobile® 2010 (Excel Mobile, Word Mobile, Outlook Mobile, PowerPoint Mobile, and Internet Explorer Mobile 6)
- Trimble SatViewer (GPS interface application)
- Trimble CellStart (WWAN configuration application)
- Microsoft My Phone with SMS text messaging (Juno 5D only)
- Camera control application
  - Flashlight mode control application
- Calculator and calendar
  - Microsoft pictures & videos
- Windows Media Player
  - Windows Live Messenger
- Microsoft Task Manager & Notes
  - Adobe Reader LE 2.5

### Barcode scanner

**1D symbologies:** EAN/UPC, GS1 Databar (limited expanded & omni-directional), Code 39, Code 128, UCC/EAN 128, ISBN, ISBT, Interleaved/Matrix/ Industrial and Standard 2 of 5, Codabar, Code 93/93i, Code 11, MSI, Plessey, Telepen, postal codes (Australian Post, BPO, Canada Post, Dutch Post, Japan Post, PostNet, Sweden Post)

**2D symbologies:** Data Matrix, PDF417, Micro PDF 417, Codablock, Maxicode, QR, Aztec

### Standard Accessories

- International AC charging kit
- USB cable
- Ultra clear screen protectors (2-pack) kit
- Wrist strap
- Quick Start Guide

### Optional Accessories

- 9-pin serial adapter
- USB Host adapter
- Capacitive stylus with tether
- External battery pack
- Vehicle charging kit
- Capacitive touch screen gloves
- Trimble headset
- Screen protectors
- External GPS antenna

## SOFTWARE COMPATIBILITY

Please refer to the [Product Compatibility matrix](#).

© 2010-2013, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, GPS Pathfinder, and Juno are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. DeltaPhase and Positions are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. Microsoft, Office Mobile, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners. PN 022501-298E (08/13)

## TECHNICAL SPECIFICATIONS

### Physical

Size	15.5 cm x 8.2 cm x 2.5 cm (6.1 in x 3.2 in x 1 in)
Weight	0.4 kg (0.84 lb) with battery
Processor	800 MHz (Juno 5B) or 1 GHz (Juno 5D), Texas Instruments DM3730
Memory	256 / 512 MB RAM (5B / 5D) and 8 / 16 GB (5B / 5D) built-in storage
Battery	3.7 V, 3.3 Ah, 12.2 Wh, Lithium-ion polymer
Power <sup>2</sup>	Low (no GPS, backlight on <sup>3</sup> ) 14 hours
	Normal (with GPS and backlight on) 8 hours

### Environmental (MIL-STD-810G)

Operating temperature	-30 °C to +60 °C (-22 °F to +140 °F)
Storage temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Humidity	90% relative humidity with temperatures between 30 °C and 60 °C (22 °F and 144 °F) Method 507.5, Procedure II
Water/dust	Protected against driving rain, water spray, dust, IEC-60529 IP65
Drop	1.22 m (4 ft.), Method 516.6, Procedure IV, Transit Drop
Vibration	Vibration resistant, Method 514.6, Procedure I & II, Category 5
Altitude	4,572 m (15,000 ft) at 23 °C (73 °F) to 12,192 m (40,000 ft) at -30 °C (-22 °F) Method 500.5, Procedure I, II & III

### Input/output

Expansion	microSD Card slot
Display	10.9 cm (4.3 in) WVGA TFT (480 x 800 pixel), capacitive, sunlight readable
Audio	Built-in microphone and speaker, record and playback utilities
I/O	USB 2.0 Host, USB Client
Radios	Bluetooth v2.1 <sup>4</sup> + EDR; Wi-Fi 802.11b/g/n UMTS / HSPA+, GSM / GPRS / EDGE UMTS Bands (WCDMA/FDD): 800/850/1900, AWS and 2100 MHz GSM Bands: 850/900/1800/1900 MHz (data and voice, Juno 5D only) <sup>5</sup>
Digital camera	8 megapixel color camera with geotagging and dual LED flash

### GPS

Channels	50 (L1 code/carrier <sup>6</sup> only)
Integrated real-time	RTCM v2.3, SBAS <sup>1</sup>
Update rate	1 Hz
Protocols	NMEA-0183, UBX binary MCX port for optional external GPS antenna

### Accuracy (HRMS)<sup>7</sup> after differential correction

Code postprocessed <sup>8</sup>	2-4 m
Real-time	2-4 m

1 SBAS (Satellite Based Augmentation System). Includes WAAS (Wide Area Augmentation System) available in North America only, EGNOS (European Geostationary Navigation Overlay System) available in Europe only, and MSAS available in Japan only.

2 Using wireless technology, such as Bluetooth or wireless LAN will consume additional battery power.

3 Backlight setting at 70% brightness.

4 Bluetooth and wireless LAN type approvals are country specific. Trimble Juno series handhelds have Bluetooth and wireless LAN approval in the USA and EU. For other countries please consult your local Reseller.

5 PTCRB, SAR, AT&T network compatible. Consult with your local reseller for more information.

6 Logging L1 carrier data for Trimble DeltaPhase™ technology postprocessing.

7 Horizontal Root Mean Squared accuracy. Requires data to be collected using vertical mounting, minimum of 4 satellites, PDOP mask at 99, SNR mask at 12 dBHz, elevation mask at 5 degrees, and reasonable multipath conditions. Ionospheric conditions, multipath signals or obstruction of the sky by buildings or heavy tree canopy may degrade precision by interfering with signal reception. Accuracy varies with proximity to base station by +1 ppm for postprocessing.

8 Requires Trimble DeltaPhase technology, as supported in Trimble GPS Pathfinder Office® software version 5.30 and later, or Trimble Positions™ Desktop add-in 10.1.1.

*Specifications subject to change without notice.*



### NORTH & SOUTH AMERICA

Trimble Navigation Limited  
10368 Westmoor Drive  
Westminster, CO 80021-2717  
USA  
+1-800-538-7800 Option 2 or  
+1-720-279-7994 Phone  
+1-720-587-4878 Fax

### EUROPE & AFRICA

Trimble Germany GmbH  
Am Prime Parc 11  
65479 Raunheim  
GERMANY  
+49-6142-2100-0 Phone  
+49-6142-2100-550 Fax

### ASIA-PACIFIC & MIDDLE EAST

Trimble Navigation  
Singapore PTE Limited  
80 Marine Parade Road  
#22-06 Parkway Parade  
Singapore, 449269  
SINGAPORE  
+65-6348-2212 Phone  
+65-6348-2232 Fax

YOUR LOCAL TRIMBLE OFFICE OR REPRESENTATIVE



[www.trimble.com](http://www.trimble.com)  
[store.trimble.com](http://store.trimble.com)