

# TRIMBLE S8 TOTAL STATION

## KEY FEATURES

**Trimble VISION** video-assisted robotic measurement

**Visual verification** with data overlay and photo documentation

**Trimble DR Plus** for longer range and fewer setups

**Specialized configuration options available**

## THE POWER TO EXCEL

Delivering major workflow innovations for both typical surveying and specialized applications, you now have the power to redefine your performance potential.

## ADVANCED SURVEYING PERFORMANCE

For typical survey tasks, choose the 1" angle accuracy and exceptional EDM range of Trimble DR Plus™. Extend your reach on the job for increased production from fewer setups.

Trimble Business Center office software provides a complete range of processing and analysis tools. Together with the Trimble S8, you have the most comprehensive solution for general surveying available today.

- **Video-Assisted Control**

Trimble VISION™ gives you the power to see everything the instrument sees without a trip back to the tripod. Direct your survey with live video images on the controller. Now you are free to capture measurements, to prism or reflectorless surfaces, with point-and-click efficiency.

- **Visual Verification**

The on-board camera integrates surveyed data with the live scene image, so you can verify the work that you've done before leaving the job. Calibrated photo documentation provides customers with deliverables they know they can trust.

## UNSURPASSED TOTAL STATION TECHNOLOGY

Trimble MagDrive™ Servo Technology provides for exceptional speed and accuracy with smooth, silent operation.

Trimble SurePoint™ Technology ensures accurate measurements by automatically correcting for unwanted movement due to wind, sinkage, and other factors.

## SPECIALIZED ENGINEERING APPLICATIONS

For precision-build applications, you need a measurement solution with optimal speed, accuracy and reliability. Combine the Trimble DR HP Precision EDM with your choice of angular accuracies and Trimble VISION or Long Range FineLock and you have the flexibility to tackle the most demanding projects.

Specialized modules in Trimble Access™ software such as Tunnels, Monitoring, or Mines provide dedicated workflows. Trimble 4D Control™ provides a comprehensive solution for the management of monitoring projects—both real time and post-processed—to rapidly detect critical structural movements.

- **Trimble FineLock™ Technology**

Detect targets without interference from surrounding prisms for high precision applications in close quarters such as rail alignment, deformation monitoring, and tunneling applications. The Trimble Long-Range FineLock option extends this functionality to 2500 m with 1 cm accuracy.

## OTHER ENGINEERING-SPECIFIC FEATURES

- Visually mark points, at greater range, in tunnels or underground mines with the Class 3R Laser Pointer.
- **Automatic Servo Focus** sets the optical focus for quick manual aiming when monitoring points in DR mode – with Trimble Access.
- Silent, frictionless movement ensures unobtrusive operation in urban or residential settings.



## TRIMBLE S8 CONFIGURATION OPTIONS

EDM	Servo Control	Angle Accuracy	Hardware Options	FineLock
DR HP	Servo only	0.5" or 1"	Tracklight	
	Robotic, Autolock	0.5" or 1"	Tracklight	o
			Trimble VISION	•
		1"	Long Range FineLock	•
			3R Laser Pointer	•
DR Plus	Robotic Only	1"	Trimble VISION	o
	Robotic, Autolock	1"	Long Range FineLock	•

KEY: • = Included    o = optional

# GENERAL SPECIFICATIONS

## PERFORMANCE (DR PLUS)

Angle measurement accuracy (Standard deviation based on DIN 18723)	0.1" (0.3 mgon)
Angle display (least count)	0.1" (0.01 mgon)
Sensor type	Absolute encoder with diametrical reading
Other distance measurement	
Accuracy (RMSE)	
Prism mode	
Standard	2 mm + 2 ppm (0.0065 ft + 2 ppm)
Standard deviation according to ISO17123-4	1 mm + 2 ppm (0.003 ft + 2 ppm)
Tracking	4 mm + 2 ppm (0.013 ft + 2 ppm)
DR mode	
Standard	2 mm + 2 ppm (0.0065 ft + 2 ppm)
Tracking	4 mm + 2 ppm (0.013 ft + 2 ppm)
Measuring time	
Prism mode	
Standard	1.2 s
Tracking	0.4 s
DR mode	
Standard	1–5 s
Tracking	0.4 s
Range	
Prism mode (under standard clear conditions <sup>1,2</sup> )	
1 prism	2,500 m (8,202 ft)
1 prism Long Range mode	5,500 m (18,044 ft) (max. range)
Shortest range	0.2 m (0.65 ft)

## DR mode

	Good (Good visibility, low ambient light)	Normal (Normal visibility, moderate sunlight, some heat shimmer)	Difficult (Haze, object in direct sunlight, turbulence)
<b>White card (90% reflective)<sup>3</sup></b>	1,300 m (4,265 ft)	1,300 m (4,265 ft)	1,200 m (3,937 ft)
<b>Gray card (18% reflective)<sup>3</sup></b>	600 m (1,969 ft)	600 m (1,969 ft)	550 m (1,804 ft)

Shortest range	1 m (3.28 ft)
DR Ranges (typically)	
Concrete	600 m–800 m (1968 ft–2624 ft)
Wood construction	400 m–800 m (1312 ft–2624 ft)
Metal construction	400 m–500 m (1312 ft–1640 ft)
Light rock	400 m–600 m (1312 ft–1968 ft)
Dark rock	300 m–400 m (984 ft–1312 ft)
Reflective foil 20 mm	1000 m (3280 ft)
DR Extended Range Mode	
White Card (90% reflective) <sup>3</sup>	2000 m–2200 m
Gray Card (18% reflective) <sup>3</sup>	900 m–1000 m
Accuracy	10 mm + 2 ppm (0.033 ft + 2 ppm)
Camera (also available as an option in the DR High Precision version)	
Chip	Color Digital Image Sensor
Resolution	2048 x 1536 pixels
Focal length	23 mm (0.07 ft)
Depth of field	3 m to infinity (9.84 ft to infinity)
Field of view	16.5° x 12.3° (18.3 gon x 13.7 gon)
Digital zoom	4-step (1x, 2x, 4x, 8x)
Exposure	Automatic
Brightness	User-definable
Contrast	User-definable
Image storage	Up to 2048 x 1536 pixels
File format	JPEG

# GENERAL SPECIFICATIONS

## EDM SPECIFICATIONS (DR PLUS)

Light source	Pulsed Laser diode 905 nm; Laser class 1
Laser pointer coaxial	Laser class 2
Beam divergence Prism mode	
Horizontal	4 cm/100 m (0.13 ft/328 ft)
Vertical	8 cm/100 m (0.13 ft/328 ft)
Beam divergence DR mode	
Horizontal	4 cm/100 m (0.13 ft/328 ft)
Vertical	8 cm/100 m (0.13 ft/328 ft)
Atmospheric correction	-130 ppm to 160 ppm continuously

## PERFORMANCE (DR HP)

Angle measurement accuracy (standard deviation based on DIN 18723)	0.5" (0.15 mgon) or 1" (0.3 mgon)
Angle display (least count)	0.1" (0.01 mgon)
Distance measurement Accuracy (RMSE)	
Prism mode	
Standard	1 mm + 1 ppm (0.003 ft + 1 ppm)
Standard deviation according to ISO17123-4	0.8 mm + 1 ppm (0.0026 ft + 1 ppm)
Tracking	5 mm + 2 ppm (0.016 ft + 2 ppm)
DR mode	
Standard measurement	3 mm + 2 ppm (0.01 ft + 2 ppm)
Tracking	10 mm + 2 ppm (0.032 ft + 2 ppm)
Measuring time	
Prism mode	
Standard	2 s
Tracking	0.4 s
Averaged observations	2 s per measurement
DR mode	
Standard	3-15 s
Tracking	0.4 s
Range (under standard clear conditions <sup>1,2</sup> )	
Prism mode	
1 prism	3,000 m (9,800 ft)
1 prism Long Range mode	5,000 m (16,400 ft)
3 prism Long Range mode	7,000 m (23,000 ft)
Shortest range	1.5 m (4.9 ft)

### DR mode

	Good (Good visibility, low ambient light)	Normal (Normal visibility, moderate sunlight, some heat shimmer)	Difficult (Haze, object in direct sunlight, turbulence)
<b>White card (90% reflective)<sup>3</sup></b>	>150 m (492 ft)	150 m (492 ft)	70 m (229 ft)
<b>Gray card (18% reflective)<sup>3</sup></b>	>120 m (394 ft)	120 m (394 ft)	50 m (164 ft)

Shortest range	1.5 m (4.9 ft)
Camera (see DR Plus page for specifications)	

## EDM SPECIFICATIONS (DR HP)

Light source	Laser diode 660 nm; Laser class 1 in Prism mode Laser class 2 in DR mode
Laser pointer coaxial (standard)	Laser class 2
Laser pointer non-coaxial (not available in all models)	Laser class 3R
Beam divergence Prism mode	
Horizontal	4 cm/100 m (0.13 ft/328 ft)
Vertical	4 cm/100 m (0.13 ft/328 ft)
Beam divergence DR mode	
Horizontal	2 cm/50 m (0.066 ft/164 ft)
Vertical	2 cm/50 m (0.066 ft/164 ft)
Atmospheric correction	-130 ppm to 160 ppm continuously

# GENERAL SPECIFICATIONS

## GENERAL SPECIFICATIONS (DR PLUS AND DR HP)

Leveling	
Circular level in tribrach	8/2 mm (8/0.007 ft)
Automatic level compensator	
Type	Centered dual-axis
Accuracy	±0.5" (0.15 mgon)
Range	±5.4' (±100 mgon)
Servo system	
	MagDrive servo technology, integrated servo/angle sensor; electromagnetic direct drive
Rotation speed	
Rotation time Face 1 to Face 2	115 degrees/s (128 gon/s)
Positioning speed 180 degrees (200 gon)	2.6 s
Clamps and slow motions	
	Servo-driven, endless fine adjustment
Centering	
Centering system	Trimble 3-pin
Optical plummet	Built-in optical plummet
Magnification/shortest focusing distance	
	2.3x/0.5 m to infinity (1.6 ft to infinity)
Telescope	
Magnification	30x
Aperture	40 mm (1.57 in)
Field of view at 100 m (328 ft)	2.6 m at 100 m (8.5 ft at 328 ft)
Shortest focusing distance	1.5 m (4.92 ft) to infinity
Illuminated crosshair	Variable (10 steps)
Autofocus	
	Standard
Tracklight built in	
	Not available in all models
Operating temperature	
	-20 °C to +50 °C (-4 °F to +122 °F)
Dust and water proofing	
	IP55
Humidity	
	100% condensing
Power supply	
Internal battery	
	Rechargeable Li-Ion battery 11.1 V, 5.0 Ah
Operating time <sup>4</sup>	
One internal battery	Approx. 6.5 hours
Three internal batteries in multi-battery adapter	Approx. 18 hours
Robotic holder with one internal battery	13.5 hours
Operating time with video robotic <sup>4</sup>	
One battery	5.5 hours
Three batteries in multi-battery adapter	17 hours
Weight	
Instrument (Servo/Autolock <sup>®</sup> )	5.15 kg (11.35 lb)
Instrument (Robotic)	5.25 kg (11.57 lb)
Trimble CU controller	0.4 kg (0.88 lb)
Tribrach	0.7 kg (1.54 lb)
Internal battery	0.35 kg (0.77 lb)
Trunnion axis height	196 mm (7.71 in)
Communication	
	USB, Serial, Bluetooth <sup>®5</sup>
Security	
	Dual-layer password protection

## ROBOTIC SURVEYING

Autolock and Robotic range <sup>2</sup>	
Passive prisms	500–700 m (1,640–2,297 ft)
Trimble MultiTrack Target	800 m (2,625 ft)
Autolock pointing precision at 200 m (656 ft) (standard deviation) <sup>2</sup>	
Passive prisms	<2 mm (0.007 ft)
Trimble MultiTrack™ Target	<2 mm (0.007 ft)
Shortest search distance	
	0.2 m (.65 ft)
Search time (typical) <sup>6</sup>	
	2–10 s

## FINELOCK

Available on Autolock and Robotic versions	
Pointing precision at 300 m (980 ft)	
(standard deviation) <sup>2</sup>	<1 mm (0.003 ft)
Range to passive prisms (min–max) <sup>2</sup>	
	20 m–700 m (64 ft–2,297 ft)
Minimum spacing between prisms	
at 200 m (656 ft)	0.8 m (2.625 ft)
Long Range (not available in all models)	
Pointing precision at 2,500 m (8,200 ft)	
(standard deviation) <sup>2</sup>	<10 mm (0.039 ft)
Range to passive prisms (min.–max.) <sup>2,7</sup>	
	20 m–2,500 m (64 ft–8,200 ft)
Minimum spacing between prisms	
at 2,500 m (8,200 ft)	<10.0 m (32.808 ft)

## GPS SEARCH/GEOLOCK WITH TRIMBLE MULTITRACK TARGET

GPS Search/GeoLock	360 degrees (400 gon)
	or defined horizontal and vertical search window
Solution acquisition time	
	15–30 s <sup>8</sup>
Target re-acquisition time	
	<3 s
Range	
	Autolock and Robotic range limits

1 Standard clear: No haze. Overcast or moderate sunlight with very light heat shimmer.  
 2 Range and accuracy depend on atmospheric conditions, size of prisms and background radiation.  
 3 Kodak Gray Card, Catalog number E1527795.  
 4 The capacity in -20 °C (-5 °F) is 75% of the capacity at +20 °C (68 °F).  
 5 Bluetooth type approvals are country specific. Contact your local Trimble Authorized Distribution Partner for more information.  
 6 Dependent on selected size of search window.  
 7 Uses a combination of Standard and Long Range FineLock.  
 8 Solution acquisition time is dependent upon solution geometry and GPS position quality.

© 2007–2013, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and Autolock are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. 4D Control, Access, FineLock, MagDrive, MultiTrack, SurePoint, and VISION are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. PN 022543-410G (06/13)



Specifications subject to change without notice.



TRIMBLE AUTHORIZED DISTRIBUTION PARTNER

### NORTH AMERICA

Trimble Navigation Limited  
 10368 Westmoor Dr  
 Westminster CO 80021  
 USA

### EUROPE

Trimble Germany GmbH  
 Am Prime Parc 11  
 65479 Raunheim  
 GERMANY

### ASIA-PACIFIC

Trimble Navigation  
 Singapore Pty Limited  
 80 Marine Parade Road  
 #22-06, Parkway Parade  
 Singapore 449269  
 SINGAPORE

